



Specifications Sylvania LED Downlight  
Start IP44 150 Aluminium White 12W  
1200lm 74D - 830 Warm White |  
Cutout 150mm - IP54 - Dimmable

[View Product](#)

## General Information

|                          |                                |
|--------------------------|--------------------------------|
| SKU                      | 255208                         |
| EAN                      | 5410288303321                  |
| Manufacturer Code        | 30332                          |
| Brand                    | Sylvania                       |
| Manufacturer Name        | ST DNLT 150 IP54 1200 830 DALI |
| Any Lamp all-in warranty | 5 Years                        |
| Average Lifetime (h)     | 100000                         |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 1x18               |
| Wattage                     | 12W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |

|                       |                                    |
|-----------------------|------------------------------------|
| Light colour options  | Single Color                       |
| Beam Angle (degree)   | 74                                 |
| Luminous Flux (Lumen) | 1200lm                             |
| Lumen per watt        | 100                                |
| Power factor          | >0.98                              |
| Unified Glare Rating  | < 25 - for hallways and staircases |
| Optical Cover         | Opal                               |
| Product Type Category | LED Downlight                      |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 150                    |
| IP-Rating              | IP54                   |
| Impact Protection (IK) | IK07 - 2 joules        |
| Operating Temperature  | -10 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 45  |
| Diameter (mm) | 165 |

## Why Any-lamp?

## Sensor Information

Type of sensor



Order from the **largest lighting specialist** in Europe

No Sensor



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

