



**Specifications Noxion LED Panel Delta Pro V5 28W 3920lm - 840 Cool White | 60x60cm - UGR <19 - Sidelit - TRIAC Dimmable**

[View Product](#)

## General Information

|                          |                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------|
| SKU                      | 257841                                                                                   |
| EAN                      | 8719157073738                                                                            |
| Manufacturer Code        | 8719157073738                                                                            |
| Brand                    | Noxion                                                                                   |
| Manufacturer Name        | Noxion LED Panel Delta Pro V5 28W 3920lm 4000K 600*600 UGR<19 Sidelit - TRIAC dimmab NDL |
| Any Lamp all-in warranty | 6 Years                                                                                  |
| Average Lifetime (h)     | 100000                                                                                   |
| Series                   | Delta Pro                                                                                |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 4x18            |
| Wattage                     | 28W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Dimmable        |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |

|                        |                   |
|------------------------|-------------------|
| Luminous Flux (Lumen)  | 3920lm            |
| Lumen per watt         | 140               |
| IP-Rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Fixture Connection     | Push Terminal     |
| Finish of Reflector    | Frosted           |
| Power factor           | >0.90             |
| Product Type Category  | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -20 to +40                     |
| Colour of the Fixture | White                          |
| Housing               | Aluminium, Metal               |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 10      |

## Why Any-lamp?

### Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation


 Up to **7 years warranty**


**Easy** return process