



**Specifications Philips LED Panel  
TrueBlend 26W 4200lm - 940 Cool  
White | 120x30cm - UGR < 18 - Best  
Colour Rendering - Dimmable - Motion  
and Light Sensor**

[View Product](#)

## General Information

|                          |                                          |
|--------------------------|------------------------------------------|
| SKU                      | 251915                                   |
| EAN                      | 8720169621978                            |
| Manufacturer Code        | 8720169621978                            |
| Brand                    | Philips                                  |
| Manufacturer Name        | RC453B 42S/940 DLO 9010 U4 L1200 W300B30 |
| Any Lamp all-in warranty | 5 Years                                  |
| Average Lifetime (h)     | 50000                                    |

## Technical Information

|                             |                                        |
|-----------------------------|----------------------------------------|
| Technology                  | LED Integrated                         |
| Replaces (Watt)             | 2x36                                   |
| Wattage                     | 26W                                    |
| Voltage (V)                 | 220-240                                |
| Dimmable                    | Dimmable when using a Dimmable Ballast |
| Colour Code                 | 940 Cool White                         |
| Colour temperature (Kelvin) | 4000 Cool White                        |
| Colour Rendering (Ra)       | 90-99                                  |
| Colour of Light             | White                                  |
| Light colour options        | Single Color                           |
| Luminous Flux (Lumen)       | 4200lm                                 |

|                        |                    |
|------------------------|--------------------|
| Lumen per watt         | 162                |
| IP-Rating              | IP20               |
| Impact Protection (IK) | IK03 - 0.35 joule  |
| Fixture Connection     | Screwless terminal |
| Power factor           | >0.90              |
| Product Type Category  | LED Panel          |

## Fixture Information

|                       |                    |
|-----------------------|--------------------|
| Mounting Method       | Recessed           |
| Unified Glare Rating  | < 18               |
| Optical Cover         | PC (Polycarbonate) |
| Operating Temperature | 0 to +25           |
| Emergency Lighting    | No Emergency Unit  |
| Colour of the Fixture | White              |
| Housing               | Steel              |
| Colour of material    | White              |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1200     |
| Width (mm)     | 300      |
| Height (mm)    | 75       |

## Why Any-lamp?

## Sensor Information

 Type of sensor

Order from the **largest lighting specialist** in Europe  
Light Sensor, Motion Sensor

 **Customised** quotation



Up to **7 years warranty**



**Easy** return process

